

waterproof exit switch

IEC06



The Alpro Waterproof Exit Switches are available in Natural Aluminium with and without LED and two different switch plate sizes – MK 1 gang and Narrow Style for flush or surface mounting. These switches offer fully weatherproofed IP68 functions. Requiring only light pressure to operate they are tested to in excess of 50⁶ cycles.



No Moving Parts

Solid state Piezo technology

Waterproof – IP68 Certified

Highest certification available

Tamper and Vandal Resistant

Switch Activation Time
One shot 120m sec.

Cycle Tested

50⁶ operations

Electrical Features

Normally open
Max 0.2A @ 24v AC/DC
(1.0A model on request)

Intrinsically Safe

Switches without LED
UL certificated

Approvals

CE and UL

DESCRIPTION

- SML Switch - Green LED
- Natural Anodised Exit Switch – MK 1 gang switch plate
- Natural Anodised Exit Switch – Narrow style switch plate
- SMA Switch - Non LED - Intrinsically Safe
- Natural Anodised Exit Switch – MK 1 gang switch plate
- Natural Anodised Exit Switch – Narrow style switch plate

Accessories

- Surface mount housing for MK 1 gang
- Surface mount housing for Narrow Style


CODE

IEC06/2N
IEC06/2N/NS


IEC06/1N
IEC06/1N/NS

IEC0610-1
IEC0620-1


SML Switch - LED



To drive LED
Yellow = +ve
Blue = -ve





Narrow style plate dimensions




Narrow style surface housing - brushed aluminium

SMA Switch - Non LED



Standard MK1 gang plate dimensions



MK1 gang surface housing - brushed aluminium