



Durante l'attivazione
 When switching on
 Durant l'activation
 Tijdens de inschakeling
 Während der Aktivierung
 Durante la activación
 Durante a activação

- * Pulsante comando apriporta locale
- * Local lock-release button
- * Bouton commande ouvre-porte local
- * Bedieningsknop lokale deuropener
- * Lokale Türöffnertaste
- * Pulsador abrepuertas local
- * Botão de comando abertura da porta local

Per maggiori informazioni sulle distanze vedi MT/KIT/14.
 For further information on distances, see MT/KIT/14.
 Pour plus d'informations sur les distances, voir MT/KIT/14.
 Zie voor meer informatie over de afstanden MT/KIT/14.
 Weitere Informationen zu den Abständen finden Sie MT/KIT/14.
 Para mayor información sobre las distancias, véanse MT/KIT/14.
 Para mais informações sobre as distâncias, consultar MT/KIT/14.

	A (max)	B (max)	C (max)
0,5 mm ² (Ø 0,8 mm - Ø 8/10 AWG 20)	20 m (65 feet)	25 m (85 feet)	150 m (495 feet)
1 mm ² (Ø 1,2 mm - Ø 12/10 AWG 17)	40 m (130 feet)	50 m (165 feet)	150 m (495 feet)
1,5 mm ² (Ø 1,4 mm - Ø 14/10 AWG 15)	60 m (195 feet)	100 m (325 feet)	150 m (495 feet)
0,28 mm ² (Ø 0,6 mm - Ø 6/10 AWG 23)			150 m (495 feet)
1 mm ² (Ø 1,2 mm - Ø 12/10 AWG 17)			100 m (325 feet)
UTP5 Cat 5 0,2 mm ² (Ø 0,5 mm - Ø 5/10 AWG 24)			150 m (495 feet)
Comelit Art. 4576 / Art. 4578 0,5 mm ² (Ø 0,8 mm - Ø 8/10 AWG 20)			150 m (495 feet)
2,50 mm ² (Ø 1,8 mm - Ø 18/10 AWG 13)	100 m (325 feet)	150 m (495 feet)	

