

## DATA SHEET

COD. **4586/6D**

### VIDEO CENTRAL POWER SUPPLY FOR COMELBUS DIGITAL SYSTEM.

To be inserted in the digital video door entry system, it carries out its functions by reading the bus controls. It supplies 20V DC (1.2 A) timed voltages for monitors (maximum of two) and 13V DC (300 mA) for TV cameras. Complete with protection circuit against short-circuits and overloads, fitted with two LEDs to indicate the presence of voltages. Also fitted with LEDs, jumpers and programming connector. 24V AC input power supply (use Art.1195).Dimensions: 140x140x67 mm (8 DIN modules).



#### Compatibility

Comelbus system:	Yes
Comtel system:	Yes

#### Mounting/Installation

Wall-mounted:	Yes
Surface-mounted:	Yes
DIN rail mounted:	Yes
DIN modules (no.):	8

#### Audio/video specifications

Audio system:	No
Audio/video system:	Yes

#### Connectivity

Stabilised output:	Yes
--------------------	-----

#### Technical properties

Temperature range:	0 / 40
--------------------	--------

#### Electrical specifications

Switching power supply:	Yes
Direct voltage output A (V):	14
Direct voltage output B (V):	20
Maximum power delivered:	32 W

#### General info

EAN product code:	'8023903037692
-------------------	----------------

# DATA SHEET

Intrastat code:	85176910
Product height (mm):	105
Product width (mm):	140
Product depth (mm):	51,5

## Packaging

Single pack height (mm):	94
Single pack width (mm):	146
Single pack weight (g):	601
Single pack depth (mm):	146
Single pack volume (dm3):	2,004