

## D5501GB STANDARD KIT - 1 DWELLING

The standard kit for one dwelling includes:

- ◆ 1 single dwelling caller unit D5801.
- ◆ 1 transmitter/receiver controller: D5200.
- ◆ 1 standard handset with mains recharging base D5130GB.
- ◆ Manuals, installation accessories, screws and batteries.



## D5601GB STANDARD 3-FUNCTION KIT 1 DWELLING FOR DOOR & GATE

The standard kit for one dwelling includes:

- ◆ 1 outdoor caller unit for one dwelling with armoured cover: D5801 + DB601.
- ◆ 1 transmitter/receiver controller: D5200.
- ◆ 1 3-function mobile handset unit: D5131GB.
- ◆ Manuals, installation accessories, screws and batteries.



## D5731GB STANDARD 3-FUNCTION KIT 1 DWELLING FOR DOOR & GATE WITH KEYPAD & TAG

The standard kit for one dwelling includes:

- ◆ 1 outdoor caller unit with keypad for one dwelling with armoured cover: D5821 + DB721.
- ◆ 1 tag
- ◆ 1 transmitter/receiver controller: CTS5200.
- ◆ 1 3-function mobile handset unit: D5131GB.
- ◆ Manuals, installation accessories, screws and batteries.



## THE BENEFITS FOR THE USER

- ◆ Can be used to welcome visitors and control the following from inside the dwelling:
  - 1 electrical latch or lock (pedestrian access),
  - 1 main gate automatic control system (car access),
  - outside lighting\*\*.
- ◆ Interior handset unit can be placed anywhere in the home (radio-operated).
- ◆ Mobile handset unit.
- ◆ Unlimited number of handsets.
- ◆ Handsfree and hand-held operation.
- ◆ Offline operation.
- ◆ LCD screen displaying:
  - status of the latch or main gate (open/closed) if position contact connected,
  - status of batteries,
  - quality of radio reception (range),
  - audio level setting,
  - status (ON/OFF) of outside lighting.
- ◆ 3 types of ring tone selectable.

## INSTALLATION BENEFITS

- ◆ Complete kit for fitting in the home or office.
- ◆ No wiring between the main gate or door pillar and the mobile handset unit.
- ◆ No mains connection: operates on batteries supplied (controller and mobile handset unit).
- ◆ 4-year battery life (in typical conditions of use).
- ◆ Operating mechanism built into the controller for all types of main gate automatic systems fitted with a manual operating mechanism requiring dry contact initiation and electrical 12 volt latches or locks (12 V/1.5 A max.).
- ◆ DynaPass® failsafe multi-frequency radio transmission\* (up to 400 m free field range\*).
- ◆ Factory-programmed handset/controller radio recognition.

\* Variable according to installation and environmental conditions.  
\*\* With receiver D5300.