# FIRST CHOICE

A carefully selected range of advanced, reliable high quality products for medium and high security applications. All are guaranteed for continuous operation and are stocked by distributors offering next-day delivery

## MONITORED ANSI ELECTRIC STRIKE ES3100

- Stainless steel striker holds up to 1,350kg
- Deep jaw accepts 19.05mm latch bolt
- Compact stainless steel body 30mm deep
- Low current consumption 175mA at 12vDC
- Rapid Fail Open Fail Secure function changeover
- Dual monitoring latch bolt and solenoid
- CE and UL approved tested to 1 million cycles

## HIGH SECURITY DEADLOCKING SOLENOID BOLT

#### JL38S

- Stainless steel construction holds up to 2,000kg
- Mortice and Surface fitting 37.5mm(w) x 41mm(d)
- Dual monitoring bolt and door position switch
- Automatic voltage adjustment from 12v to 24vDC
- Low current consumption 250mA at 12vDC
- CE approved tested to 1 million cycles

#### WRAPAROUND ELECTRIC STRIKE

#### ES3500

- Stainless steel striker holds up to 1,350kg
- Deep jaw accepts 19.05mm latch bolt
- Compact stainless steel body 30mm deep
- Low current consumption 175mA at 12vDC
- Rapid Fail Open Fail Secure function changeover
- Dual monitoring latch bolt and solenoid
- · Heavy Duty stainless steel face plate
- CE approved

#### **ELECTRIC RIM STRIKE**

#### ES150

- Stainless steel striker holds up to 1,350kg
- Compact aluminium body 36mm depth
- Low current consumption 243mA at 12vDC
- Rapid Fail Open Fail Secure function changeover
- Weather resistant IP56 protection
- CE approved

## Locking Solutions





JF382

FS3100





ES150

ES3500

#### SURFACE MOUNT ELECTRIC LOCK

#### ES600

- Holding force 1,350kg
- Opens freely with up to 545kg side pressure
- · Self-latching jaw
- Interlock between rotating jaw and strike plate
- Deadlock protected against tampering
- Dual monitoring latch bolt and solenoid
- 12/24vDC convertible
- · Vertical or horizontal mounting
- Manual over rides and housing options
- · Weather resistant IP56 protection
- CE and UL approved tested to 2 million cycles

#### MONITORED ELECTRIC STRIKE

#### ES2400

- Stainless steel striker holds up to 1,350kg
- Compact stainless steel body 27mm deep
- Low current consumption 175mA at 12vDC
- Rapid Fail Open Fail Secure function changeover
- Extended fixing tabs twin screw holes
- Dual monitoring latch bolt and solenoid
- Weather resistant IP56 protection
- CE and UL approved tested to 1 million cycles

### SLIMLINE DEADLOCKING SOLENOID BOLT

#### JL25R

- Stainless steel construction holds up to 1,000kg
- Mortice and Surface fitting 25mm(w) x 41mm(d)
- Dual monitoring bolt and door position switch
- Automatic voltage adjustment from 12v to 24vDC
- Low current consumption 210mA at 12vDC
- Built-in Access Automatic unlock period 8 seconds Control Processor Multiple auto relock function
- CE approved

#### **ANSI ELECTRIC STRIKE**


#### F\$110

- Stainless steel striker holds up to 1,350kg
- Compact aluminium body 35mm depth
- Low current consumption 243mA at 12vDC
- Rapid Fail Open Fail Secure function changeover
- ANSI short and long face plates (SAA and SS)
- Weather resistant IP56 protection
- CE and UL approved tested to 1 million cycles

#### DEADLATCH & PADDLE HANDLE

- ANSI dimension cut outs
- Euro or Round screw-in cylinders
- Multiple back sets
- Anti-thrust snibs
- Key-operated holdback
- · Paddle handles Pull or push, left or right
- Round, screw-in Thumb turns (SAA)





ES600


ES2400





ES11(

11 2 5 1



DEADLATCH & PADDLE HANDLE



For detailed data sheets:

Telephone 01202 676262 Facsimile 01202 680101 E-mail iec.uk@pobox.com Web site www.iecltd.co.uk INTERNATIONAL ENGINEERING COMPANY LIMITED Harwell Road Nuffield Estate Poole Dorset BH17 0BD Great Britain October 1999 IEC Limited. All rights reserved.

